

Marion County Public Works Building Inspection Division 5155 Silverton Rd NE Salem OR 97305 (503) 588-5147 Fax (503) 588-7948 http://www/co.marion.or.us

ON-SITE SYSTEM MATERIAL LIST

(DIRECTIONS & DEFINITIONS ON BACK)

ΑĽ	DRESS		TAX LOT #	
			SECTION TOWNSHIP RANGE LOT	
1.	SEPTIC TANKS			
			MATERIAL	
			MATERIAL	
	□ <u>SEPTIC/DOSING TANK</u> : □ SINGLE COMPARTMENT □ TWO COMPARTMENT □ FLOW-THROUGH			
	MFG	CAPACITY	MATERIAL	
			MFG.'S SPECS. INCLUDED	
2.	PUMPING ASSEMBLIES			
	PUMP 1: MFG.	MODEL	(INCLUDE PERFORMANCE CURVE)	
			(INCLUDE PERFORMANCE CURVE)	
	CONTROL PANEL: MFG.			
			(INCLUDE ORIFICE CALCULATIONS)	
	EFFLUENT FILTER: MFG.		•	
	DISTRIBUTION VALVE: MFG.			
3.	EFFLUENT TRANSPORT PIPING			
	☐ GRAVITY EFFLUENT SEWER: LENGT	TH DIAMETER	MATERIAL FALL (IN INCHES)	
	· · · · · · · · · · · · · · · · · · ·			
4.	DISPOSAL FIELD (DRAINFIELD)			
	DISTRIBUTION TECHNIQUE: □ EQUAL □ LOOP □ SERIAL □ PRESSURIZED			
	TOTAL LINEAR FOOTAGE:			
	DRAIN MEDIA: ☐ GRAVEL-LESS ABSO	RPTION METHOD ROCK &	PIPE DOTHER	
	TOTAL DEPTH	DEPTH BELOW PIPE	<u></u>	
	TRENCH DEPTH (FROM ORIGINAL GRO	UND SURFACE): MIN	MAX	
	CAPPING FILL DEPTH (DEPTH OF CAP):			
	SETBACKS FROM WELLS: SEPTIC TANK SAND FILTER OR ATT UNIT DRAINFIELD			
5.	DEWATERING SYSTEMS (IF REQUIRED)			
	□ CURTAIN DRAIN □ TILE DEWATERING			
	TRENCH DEPTH:			
	DRAIN MEDIA: ROCK & PIPE OTHER			
	TOTAL DEPTH DEPTH BELOW PIPE FILTER FABRIC			
	PERFORATED PIPING: DIAMETER	MATERIAL		
6.	ADVANCED TREATMENT UNITS			
	□ SAND FILTER □ RGF □ ATT: T\	/PE		

ONSITE SYSTEM MATERIAL LIST INSTRUCTION SHEET

The Onsite System Material List is a necessary and important part of the pre-permit system plans. This document allows us to catch any potential problems before the system is installed and allows you to familiarize yourself with the materials and construction requirements for the system. This form must be completed, submitted, and approved before we can issue a permit. Once approved, this document becomes part of the permit and will be used to perform the inspection of your installed septic system.

MATERIAL LIST SECTION

- **1. Tank information:** Enter septic tank, dosing tank, or septic/dosing tank information (you will not have a dosing tank if you are constructing a gravity-flow system).
 - a. Mfg: Is the name of the manufacturer who made the tank.
 - b. Capacity: Is the capacity of the tank in gallons.
 - c. Material: Is what material the septic tank is constructed from (concrete, steel, polyethylene, etc...).
- 2. **Pumping information:** This section is <u>only</u> for systems that use pumps, siphons, or effluent filters. Please enter the data as appropriate or skip this section if your system does not have any of these components. **Be sure to include manufacturer's specifications for all sections that apply.**
 - a. Pump: Enter the manufacturer (MFG) and model of the pump.
 - b. <u>Hydrosplitter</u>: If you are installing a hydrosplitter, enter the manufacturer and model. Hydrosplitter orifice selections must be obtained from the manufacturer.
 - c. Effluent filter: If you are installing an effluent filter, enter the manufacturer and model information.
 - d. <u>Distribution valve</u>: If you are installing a distribution valve, enter the manufacturer and model information.
- 3. **Effluent transport piping information:** The effluent sewer is the pipe that connects the outlet of the septic tank to the drainfield. The pressure piping is the pipe between the pump discharge and the drainfield.
 - a. Enter information about the gravity effluent sewer as follows:

Length: Is the length of the effluent sewer.

<u>Diameter</u>: The diameter of the effluent sewer.

<u>Material</u>: Is the actual material from which the pipe is made, and its specification number -- an example would be PVC 3034.

<u>Fall:</u> Is the difference in elevation, in inches, between the effluent sewer pipe at the outlet of the septic tank and

the header pipe where it leaves the d-box.

b. Enter information about pressure transport piping as follows:

<u>Length</u>: Enter the length of the pressure piping from the tank to the drainfield, the hydrosplitter, or the start of the pressure network.

Diameter: Enter the diameter of the pressure piping that you are going to use.

<u>Material</u>: Enter the actual material from which the pipe is made and its specification number -- an example would be PVC 1120.

<u>PSI</u>: Enter the pressure rating (pounds per square inch or PSI) of the pressure piping that you are going to use.

4. Disposal trenches:

- a. Distribution technique: Check the box next to the distribution technique you are going to use.
- b. <u>Total Linear Footage</u>: Is the total length of the perforated pipe, chambers, or other approved disposal media.

lt

does not include headers or other solid pipe.

- c. <u>Drain Media</u>: Check the box to indicate which media you are going to use. Include the total depth of the drainfield rock (if it is being used), and the depth of the drainfield rock below the pipe.
- d. Trench Depth: Is the minimum and maximum depth of the trench below the original ground surface.
- e. <u>Capping Fill Depth</u>: If you are constructing a capping fill drainfield, enter the depth of the fill material above the original ground surface.
- f. <u>Setbacks from Wells</u>: Enter the distance (in feet) from the well to the septic tank, to the sand filter or other treatment device, and to the drainfield.

Dewatering Systems: (If used)

- a. Check the box next to the dewatering system that is required.
- b. Trench Depth: Is the depth of the dewatering trench below the original ground surface.
- c. <u>Drain Media</u>: Check the box to indicate which media you are going to use. Include the total depth of the drainfield rock (if it is being used), and, for a curtain drain, the depth of the drainfield rock below the pipe. If a curtain drain is required, filter fabric must be placed above the drain media.
- d. <u>Perforated Piping</u>: Enter the diameter and material of the perforated piping that will be used.